



IP68

Industrial Biometric Tablet

Incore IP68 Industrial Biometric Tablet is an Android 9 rugged tablet with abundant functions. With its powerful CPU, 8 inch high-definition screen, 8000 mAh battery and comprehensive data capture options like UHF RFID (with the latest Impinj Gen2X), barcode scanning, NFC, fingerprint recognition, etc., you can find this easy-to-deploy device a valuable helper to increase productivity in retail, logistics, warehousing, identity verification, meter reading, etc.

- 
Android
- 
4G
- 
Wi-Fi
- 
Bluetooth
- 
UHF
- 
1D Barcode
- 
2D Barcode
- 
PSAM
- 
NFC
- 
Fingerprint
- 
Camera
- 
GPS

SPECIFICATION

Physical Characteristics

Dimensions	250.8 x 152.0 x 15.0 mm / 9.87 x 5.98 x 0.59 in. (for standard version)
Weight	700 g / 24.69 oz. (for standard version)
Display	8" IPS LTPS 1920 x 1200
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Power	Main battery: Li-ion, rechargeable, 8000 mAh Standby: over 500 hours Continuous use: over 10 hours (depending on user environment) Charging time: 5-7 hours (with standard AC adaptor and USB cable)
Expansion Slot	1 slot for Micro SIM card, 1 slot for Micro SIM / TF card, Optional dual PSAM card slots
Interfaces	USB 2.0 Type-C, OTG
Sensors	Accelerometer sensor, geomagnetic sensor; gyroscope
Notification	Sound, LED indicator
Audio	1 microphone; 1 speaker; receiver
Keypad	1 front key, 1 volume key, 1 power key, direction key (Optional)

Performance

CPU	Octa-core 1.8 GHz
RAM+ROM	3GB + 32GB / 4GB + 64GB
Expansion	Supports up to 256GB Micro SD (TF) card

Developing Environment

Operating System	Android 9; GMS, 90-day security updates, Android Enterprise, Zero-Touch, FOTA, Soti MobiControl, SafeUEM supported
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment

Operating	-4 °F to 122 °F / -20 °C to 50 °C
Temp. Storage	-40 °F to 158 °F / -40 °C to 70 °C
Temp. Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5 m / 4.92 ft. drops to concrete across the operating temperature range
Tumble Specification	500 x 0.5 m / 1.64 ft falls at room temperature
Sealing	IP65 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication

WLAN	Support 802.11 a/b/g/n/ac/d/e/h/i/l/k/r/v, 2.4G/5G dual-band, IPV4, IPV6; Fast roaming: PMKID caching, 802.11r, OKC; Operating Channels: 2.4G(channel 1-13), 5G(channel 36,40,44,48,52,56,60,64,100,104,108,112,116,120,124,128, 132,136,140,144,49,153,157,161,165), Depends on local regulations; Security and Encryption: WEP, WPA/WPA2-PSK (TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS, PEAP-GTC, etc.
WWAN (Europe, Asia)	2G: 850/900/1800/1900MHz, GPRS, EDGE 3G: CDMA EVDO: BCO TD-SCDMA: B34/B39 WCDMA: B1/B5/B8 4G: TDD-LTE: B34/B38/B39/B40/B41 FDD-LTE: B1/B3/B5/B7/B8/B20
WWAN(America)	3G: WCDMA: B2/B4/B5 4G: FDD-LTE: B2/B4/B5/B7/B12/B13/B17/B28A/B28B

Vo-LTE	Support Vo-LTE HD video voice call
Bluetooth	Bluetooth 4.2/4.1+HS/4.0/3.0+HS/2.1+EDR
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna

Data Collection

Camera

Rear Camera	13 MP Autofocus with flash
Front Camera	8 MP

Barcode Scanning (Optional)

Scan Engine	Zebra SE4710, Zebra SE4850
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch, Postal (KIX), etc.

RFID (Optional)

UHF

Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
------------------	---

* For detailed specification, please check P80 UHF part.

NFC

Frequency	13.56 MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4 cm

Fingerprint (Optional)

Option 1 / 2

Sensor	TCS1 / TLKINC02
---------------	-----------------

Option 3

Sensor	Optical Morpho CBM-E3
---------------	-----------------------

* For detailed specification, please check P80 Fingerprint part.

PSAM (Optional)

Card slot	2 PSAM card slots
Protocol	ISO7816