



## Primus HSM CyberVault (X2 models)

### The Hardware Security Module that combines performance and cyber security innovation

The Securosys Primus CyberVault X2 models deliver market-leading performance while meeting the highest requirements of security, availability, flexibility, and tamper protection. Integrating into existing systems is seamless, ensuring effortless commissioning and setup.

Our approach to a secure post-quantum cryptography (PQC) transition stands through the use of hybrid signatures, combining classical cryptographic and PQC algorithms while maintaining consistent throughput. This ensures a smooth and future-proof migration. The Primus CyberVault series natively supports all NIST-selected post-quantum cryptographic algorithms, including ML-DSA, SLH-DSA, ML-KEM, HSS-LMS, and XMSS, alongside the classical cryptographic algorithms RSA or ECC/ED.

The Primus HSM CyberVault series is designed for businesses of all sizes, offering scalability, high availability, and redundancy. The devices support clustering, load balancing, and failover mechanism, making them ideal for mission-critical applications where uninterrupted operation is essential.

#### Key Benefits and Model Differentiators\*

##### ★ CyberVault Pro

The **Pro** edition – like all models from the series – is equipped with a **2FA authentication mechanism and a user interface** for intuitive management. **Performance and storage are fixed**, making it a cost-efficient and reliable solution for **small to mid-sized businesses** that require **secure key management and encryption** without the need for extensive scalability.

##### ★ CyberVault Enterprise

The **Enterprise** edition provides the **most flexible model** in the CyberVault series, available in **two variants** to best fit a company's needs. It offers **upgrade options** for **enhanced performance, additional storage, or increased number of partitions**, allowing businesses to scale as their security infrastructure evolves. Designed for organizations requiring adaptability, the Enterprise model ensures long-term investment protection.

##### ★ CyberVault Max

The **Max** edition stands out as one of the **fastest HSMs on the market**, handling over **50'000 transactions per second (TPS)**. Designed for **high-performance environments**, it can scale up to **over 1'000'000 TPS** in clustered setups, delivering unmatched **speed, security, and reliability**. This makes it the ideal choice for **financial institutions, blockchain infrastructures, and demanding cryptographic workloads**.

##### ★ CyberVault Max Plus

The **Max Plus** edition pushes the limits of **hybrid performance** for PQC and classical algorithms combined, and an **impressive 30GB storage**. This model is tailored for **organizations requiring extreme security, high-speed cryptographic processing, and large-scale key storage**. It is the ultimate solution for businesses operating in highly regulated industries, large-scale cloud environments, or national security applications.

✚ **Designed, developed, and manufactured in Switzerland.**

\* For each model there are several additional features available. Please contact our sales team to learn more.

## Security Features

### Security Architecture

- / Multi-barrier software and hardware architecture with supervision mechanisms
- / Secure supply-chain

### Encryption/Authentication (extract)

- / Post-Quantum Cryptographic (PQC) algorithms  
ML-DSA, SLH-DSA, ML-KEM, HSS-LMS, XMSS
- / RSA 1024-8192, DSA 1024-8192
- / ECDSA 224-521, GF(P) arbitrary curves (NIST, Brainpool, ...)
- / ED25519, Curve25519
- / Diffie-Hellman 1024, 2048, 4096, ECDH
- / SHA-3/SHA-2 (224 - 512), SHA-1, RIPEMED-160, Keccak
- / HMAC, CMAC, GMAC, Poly 1305
- / 128/192/256-Bit AES with GCM-, CTR-, ECB-, CBC-, MAC Mode
- / Camellia, ChaCha20-Poly1305, ECIES

### Key Generation

- / Two hardware true random number generators (TRNG)
- / NIST SP800-90 compatible random number generator

### Key Management

Model	Partitions	Total Storage	Upgradeable to	
			Partitions	Total Storage
Pro	5	600MB	fixed	
Enterprise	10	2.4GB	250	30GB
Max	20	4.8GB	1000	30GB
Max Plus	100	30GB	1000	fixed

### Operation

- / Number of client connections not restricted
- / Unlimited number of backups

### Anti-Tamper Mechanisms

- / Several sensors to detect unauthorized access
- / Active destruction of key material and sensitive data on tamper
- / Transport and multi-year storage tamper protection by digital seal

### Attestation and Audit Features

- / Cryptographic evidence of audit relevant parameters (keys, configuration, hardware, states, logs, time-stamping)

### Identity-based Authentication

- / Multiple security officers (m out of n)
- / Identification based on smart card and PIN

## Networking Features

### Software Integration

- / JCE/JCA provider
- / PKCS#11 provider, OpenSSLV3
- / Microsoft CNG/KSP provider
- / RESTful API

### Networking

- / IPv4/IPv6
- / Interface bonding (LACP or active/backup)
- / Active clustering of multiple units for load-balancing and fail-over
- / Monitoring and log streaming (SNMPv2, syslog/TLS)

### Device Management

- / Local configuration (GUI, Console)
- / Remote administration (Decanus Terminal)
- / Local and remote firmware update
- / Network attached storage data transfer (WebDAV)
- / Secure log and audit
- / Enhanced diagnostic functions

## Technical Data

### Performance (transactions per second)

Signing	Pro	Enterprise	Max	Max Plus	
RSA 4096	400	500	1000	2'000	5'000
EC 256*	5'000	5'000	10'000	30'000	45'000
ED 25519	7'500	7'500	15'000	30'000	45'000
AES	7'500	7'500	15'000	30'000	45'000
ML-DSA-44	2'500	2'500	5'000	10'000	20'000

### Key creation

RSA 2048	20	40	60	80	80
----------	----	----	----	----	----

\*With maximum performance license.

### Power

- / Two redundant power supplies, hot pluggable  
100 ... 240 V AC, 50 ... 60 Hz
- / Power dissipation: 65 W (typ.), 100 W (max.)
- / Backup lithium battery: Lithium Thionyl Chloride 0.65g Li,  
IEC 60086-4, UL 1642, 3.6V

### Interfaces

- / 4 Ethernet RJ-45 ports with 1 Gbps (rear)
- / 2 SFP+ slots for optical 10Gbps Ethernet modules (rear)
- / 2 Console ports (RJ45, front/rear)
- / 2 USB-A management ports (front/rear)
- / 1 USB-C management port (rear)
- / 3 Smart card slots

### Controls

- / 3 slots for Securosys security smart cards
- / 4 LEDs for system and interface status (multicolor)
- / Touch screen for configuration
- / Console interface
- / Optional Decanus Terminal for remote administration

### Environmental Test Specifications

- / EMV/EMC: EN 55022, EN 55024, FCC Part 15 Class B
- / Safety: IEC 62368-1

### Specifications

- / Temperature ranges (IEC 60068-2-1 Ad, IEC 60068-2-2 Bd):  
storage -20 ... +60 °C; operation 0 ... +35 °C
- / Humidity (IEC 60068-2-78 Cab): 40 °C, 93% RH, non-condensing
- / MTBF (RIAC-HDBU-217Plus) at  $t_{amb}=25$  °C: >100 000 h
- / Dimensions (w×h×d) 417×44×365 mm (1U 19" EIA standard rack)
- / Weight 7.5kg

### Certifications

- / FIPS140-3 Level 3 (in certification)
- / Common Criteria EAL4+ (in certification)
  - CC EN 419221-5 eIDAS protection profile
  - CC EN 419241-2 Sole Control (SAM)
- / CE, FCC, UL

Visit our website



#### HEADQUARTER

Securosys SA  
Max-Högger-Strasse 2  
8048 Zürich  
Switzerland

+41 44 552 31 00  
info@securosys.com  
www.securosys.com



Front



Rear

We strive to continuously improve our offerings and therefore reserve the right to change specifications without notice. Designed and manufactured in Switzerland.

Copyright ©2025 Securosys SA. All rights reserved. Ev1.0